

QHB-LED Ambient Temp Hi Bay

Light Up Your Bulk/Dock Areas With The State-of-the-Art QHB Fixture.

- Heat is the main problem with using LED fixtures in uncontrolled ambient environments.
- The QHB was designed with this in mind allowing you to maximize performance, and reduce wattage in unconditioned areas.

Instant Re-Strike + Controls = Cost Savings

- The QHB's LED engine re-strikes instantly allowing for control by occupancy sensors with no lengthy warm up times.
- The QHB's low wattages combined with occupancy sensors can drastically reduce the energy usage in your warehouse and create compelling paybacks.

Optics

- Bad lighting is often characterized by having spots that are either too bright or too dark.
- We took great care in designing the optics for the QHB to ensure an even distribution with a low max/min ratio.

Adaptive Thermal Technology

- Patent pending housing has 6.9 ft² of heat sinking surface area per linear foot of housing. This allows the length of the fixture to be increased to reduce component temperature for extreme environments.

Why [P2]? It's Simple, Our Experience.

- While many manufacturers promise long life and maintenance free performance from their LED products, it takes a real expert to create a fixture that delivers on that promise.
- We have spent months designing, testing, re-designing and perfecting our LED line in order to give you the highest quality products that deliver on the promises of LED.


Energy Efficient LED Fixture



Application



QHB - 145W - 277 - 60C - 700 - 50K - AAO



Model

QHB = LED Hi Bay

Input Watts

87W = 87 Watt (36 Chip)
145W = 145 Watt (60 Chip)

Voltage(1)

277 = 277 Volt
347 = 347 Volt
480 = 480 Volt

Note

(1) Contact factory for assistance with ordering 120V fixtures.

Qty. of LED Chips

36C = 36 Chip Board
60C = 60 Chip Board

Drive Current

700 = 700 mA Drive Current

Color Temperature

50K = 5000 Kelvin

Optics

OAO = Open Area Optic
AAO = Asymmetrical Aisle Optics

Occupancy Sensor

3VH = 360° View Hi Bay
3VL = 360° View Lo Bay
3HVB = 360° View Hi Bay Bi Level
3LVB = 360° View Lo Bay Bi Level

Cord and Plug

C8 = 8' Cord
PQC15 = 15' Quick Connect
C8/515 = 8' Cord & 120 V Plug

Mounting

10GYSH = 10' Y-Gripple
Snap Hook Hangers