

LED Site Lighter Installation Instructions

Warnings and Safety Information—Please read carefully!

- Risk of fire and/or electric shock. This product is to be installed by a qualified electrician only. Light fixture installation requires knowledge of lighting luminaire electrical systems. Do not attempt if unqualified.
- This fixture is to be installed only in areas with construction features consistent with drawings on this sheet.
- Luminaire wiring, ballast or other electrical parts may be damaged when drilling or cutting for installation of canopy fixture. Check for concealed wiring and components prior to drilling.
- Do not expose wiring to sheet metal edges or other sharp objects to prevent damage.
- Install in accordance with all national and local electrical codes. Manufacturer assumes no responsibility for the improper installation or application of this fixture.
- Contact the manufacturer for any questions or concerns regarding installation of this fixture.
- To avoid damage to diodes AC power supply must be turned off before connecting or disconnecting secondary wiring connectors.

Included Materials

A: (1) LED Site Lighter Fixture with Slip Fitter

Installation Instructions

- Luminaire is intended to be mounted to a 2-3/8" OD (2" Pipe Size) x Min 5" Long Tenon
- Slip luminaire over tenon, passing lead wires through the appropriate splicing area, adjust the (6) set screws to level luminaire, then tighten all (6) set screws to 150 in-lb in an alternating fashion. Re-check torque on all set screws.
- Check supply voltage against luminaire rating label. Splice luminaire lead wires to branch circuit supply wires. If spliced in pole, provide appropriate means of strain relief, such as a cable tie.

