

Part #	Image	Description
PMK		Adjustable Pole Mount Bracket
WMK		Adjustable Wall Mount Bracket (New replacement for MKB)
ADF		Adjustable Slip Fitter for 2-3/8" OD Tenon (New replacement for ASF)
WMSSA (aka MKA)		Wall Mount Plate with 10" Bolt on Arm
WMH		Wall Mount Plate with 2-3/8" Tenon
PMV		Mid-pole Vertical Tenon Adapter 11 1/2"
BO8		8" Bolt on Arm
BO2		2" Bolt on Arm
BO10		10.75" Bolt on Arm
BO8R		8" Bolt on Arm for ROUND Poles
TVA4		Tenon Mount Adaptor - 4" Square Pole to 2-3/8" OD Tenon
TVA5		Tenon Mount Adaptor - 5" Square Pole to 2-3/8" OD Tenon
TVA6		Tenon Mount Adaptor - 6" Square Pole to 2-3/8" OD Tenon

Part #	Image	Description
TVA4R		Tenon Mount Adaptor - 4" Round Pole to 2-3/8" OD Tenon
TVA5R		Tenon Mount Adaptor - 5" Round Pole to 2-3/8" OD Tenon
TVA6R		Tenon Mount Adaptor - 6" Round Pole to 2-3/8" OD Tenon
TH190		Pole Top Adaptor - Single 2-3/8" OD Tenon
TH2180		Pole Top Adaptor - Double 2-3/8" OD Tenons, 180
TH290		Pole Top Adaptor - Double 2-3/8" OD Tenons, 90
TH390		Pole Top Adaptor - Triple 2-3/8" OD Tenons, 90
TH3120		Pole Top Adaptor - Triple 2-3/8" OD Tenons, 120
TH490		Pole Top Adaptor - Quad 2-3/8" OD Tenons, 90
PTASSA 8"		Poletop Adaptor - 2-3/8" OD Tenon to Bolt on Arm

\*\*Below is a list of fittings that we would recommend to consider for mounting P2 outdoor linear fluorescent fixtures to existing poles. However, careful consideration must be given to the site conditions prior to ordering, that is the responsibility of the Contractor/Distributor. A calculation of the EPA and weight for each proposed P2 fixture configuration must be made to determine if the existing pole is rated for the proposed solution. The thickness, height, and existing condition of each pole, and the geographic location of the site will all be significant variables to determine the appropriate rating for a proposed solution. P2 will supply, upon request, any information relative to our fixtures and brackets required for the calculations.

**WALL MOUNT**

Fixture Type	Mount Angle	Configuration Type	Option 1	Option 2
<b>Wallmount</b>				
EST	ADJUSTABLE OR STRAIGHT	SINGLE	WMK	WMH, ADF
EWT	ADJUSTABLE OR STRAIGHT	SINGLE	WMK	WMH, ADF
EWX	ADJUSTABLE OR STRAIGHT	SINGLE	WMK	WMH, ADF
EFT	ADJUSTABLE OR STRAIGHT	SINGLE	WMK	WMH, ADF
EST	STRAIGHT	SINGLE	WMK	WMSSA
EWT	STRAIGHT	SINGLE	WMK	WMSSA
EWX	STRAIGHT	SINGLE	WMK	WMSSA
EFT	STRAIGHT	SINGLE	WMK	WMSSA

\*Wallplate can be ordered by size to cover old fixture footprint

**POLE MOUNT**

**4" Square Steel Straight**

(USE ADF FOR EACH FIXTURE IF EXISTING 2 3/8" TENON EXISTING)

Fixture Type	Configuration Type		Option 1	Option 2
EST	ADJUSTABLE OR STRAIGHT	SINGLE	PMK	TVA4 + TH190 + (1)ADF
		DOUBLE 180	(2)PMK	TVA4 + TH2180 + (2)ADF
		DOUBLE 90	(2)PMK	TVA4 + TH290 + (2)ADF
		TRIPLE 90	(3)PMK	TVA4 + TH390 + (3)ADF
		TRIPLE 120	TVA4 + TH3120 + (3) ADF	
		QUAD 90	(4)PMK	TVA4 + TH490 + (4)ADF
		MID-HEIGHT MOUNT	PMK	
EWT	ADJUSTABLE OR STRAIGHT	SINGLE	PMK	TVA4 + TH190 + (1)ADF
		DOUBLE 180 (BACK TO BACK)	(2)PMK	TVA4 + TH2180 + (2)ADF
		MID-HEIGHT MOUNT	PMK	
EFT	ADJUSTABLE OR STRAIGHT	SINGLE	PMK	TVA4 + TH190 + (1)ADF
		DOUBLE 180 (BACK TO BACK)	(2)PMK	TVA4 + TH2180 + (2)ADF
		MID-HEIGHT MOUNT	PMK	
EST	STRAIGHT	SINGLE	PMK	BO8
		DOUBLE 180	(2)PMK	(2)BO8
		DOUBLE 90	(2)PMK	(2)BO8
		TRIPLE 90	(3)PMK	TVA4 + PTASSA + (3)BO8
		TRIPLE 120	TVA4 + TH3120 + (3) ADF	
		QUAD 90	(4)PMK	TVA4 + PTASSA + (4)BO8
		MID-HEIGHT MOUNT	PMK	BO8
EWT	STRAIGHT	SINGLE	PMK	BO8
		DOUBLE 180 (BACK TO BACK)	(2)PMK	(2)BO8
		MID-HEIGHT MOUNT	PMK	BO8
EFT	STRAIGHT			

\*(X) = QUANTITY

**5" Square Steel Straight**

Use TVA5

**6" Square Steel Straight**

Use TVA6

**POLE MOUNT**

**4" Round Steel Straight**

(USE ADF FOR EACH FIXTURE IF EXISTING 2 3/8" TENON EXISTING)

Fixture Type	Configuration Type		Option 1	Option 2
EST	ADJUSTABLE OR STRAIGHT	SINGLE	TVAR4 + ADF	B04R4-ADF
		DOUBLE 180	TVAR4 + TH2180 + (2)ADF	(2)B04R4-ADF
		DOUBLE 90	TVAR4 + TH290 + (2)ADF	(2)B04R4-ADF
		TRIPLE 90	TVAR4 + TH390 + (3)ADF	(3)B04R4-ADF
		TRIPLE 120	TVAR4 + TH3120 + (3) ADF	(3)B04R4-ADF
		QUAD 90	TVAR4 + TH490 + (4)ADF	(4)B04R4-ADF
	MID-HEIGHT MOUNT		B04R4-ADF	
EWT	ADJUSTABLE OR STRAIGHT	SINGLE	TVAR4 + ADF	B04R4-ADF
		DOUBLE 180 (BACK TO BACK)	TVAR4 + TH2180 + (2)ADF	(2)B04R4-ADF
		MID-HEIGHT MOUNT		B04R4-ADF
EFT	ADJUSTABLE OR STRAIGHT	SINGLE	TVAR4 + ADF	B04R4-ADF
		DOUBLE 180 (BACK TO BACK)	TVAR4 + TH2180 + (2)ADF	(2)B04R4-ADF
		MID-HEIGHT MOUNT		B04R4-ADF
EST	STRAIGHT	SINGLE	BO8R4	TVAR4 + ADF
		DOUBLE 180	(2)BO8R4	TVAR4 + TH2180 + (2)ADF
		DOUBLE 90	(2)BO8R4	TVAR4 + TH290 + (2)ADF
		TRIPLE 90	TVAR4 + TH390 + (3)ADF	(3)BO8R
		TRIPLE 120	TVAR4 + TH3120 + (3) ADF	(3)BO8R
		QUAD 90	TVAR4 + TH490 + (4)ADF	(4)BO8R
	MID-HEIGHT MOUNT	BO8R4		
EWT	STRAIGHT	SINGLE	PMK	TVAR4 + ADF
		DOUBLE 180 (BACK TO BACK)	(2)PMK	TVAR4 + TH2180 + (2)ADF
		MID-HEIGHT MOUNT	PMK	
EFT	STRAIGHT			

\*(X) = QUANTITY

**5" Round Steel Straight**

Use TVAR5, BO4R5-ADF and BO8R5

**6" Round Steel Straight**

Use TVAR6, BO4R6-ADF and BO8R6